

IN THE CLAIMS:

Please cancel claim 60-73

Please add the following claims:

#1 1/86. A tool assembly adapted for insertion into a well or other hole to direct monitoring of at least one condition existing in the well or other hole, the tool comprising:  
an elongated housing with first and second ends, where the second end includes an opening sized to receive and provide access to one or more energy storage units insertable therein;

a computing unit positioned within the elongated housing and connectable to at least one sensor which is configured to provide a sensor reading of at least one monitored condition, the sensor reading comprising a sensor output signal including sensor reading data corresponding to the at least one monitored condition, the computing unit being configured to receive and process the sensor output signal;

a main circuit board positioned within the elongated housing, the main circuit board including at least one electrical contact positioned to contact one or more electrodes of the one or more energy storage units components upon insertion through the opening of the second end;  
and

an electrical assembly including the at least one electrical contact and an electrical circuit configured to conduct electrical signals between the second end of the elongated housing and the computing unit.

2/87. The assembly of claim 86 further including a cable component configured for engaging and disengaging the second end of the elongated housing, where engagement of the cable component with second end establishes a connection with terminal end of a cable, the cable configured to include at least one of:

a plurality of communication lines which are operably connected through the electrical assembly with the computing unit so that the computing unit is capable of directing at least one communication function selected from (i) transmission of a communication signal via the communication lines and (ii) receiving a communication signal via the communication lines,

a plurality of power lines which are operably connected to the computing and which conduct power from the remote power source; and

Ant  
a first fluid conductive path extending along the length of the cable, such that when the elongated housing and cable component are assembled and the at least one sensor is a pressure sensor, the pressure sensor is capable of taking pressure readings adjusted for atmospheric pressure.

3 88. The assembly of claim 86 wherein the at least one electrical contact comprises a spring loaded contact extending from the main circuit board towards the second end of the elongated housing and positioned to contact one or more of the electrodes of the one or more energy storage units components upon insertion through the opening of the second end.

4 89. The assembly of claim 86 further wherein the electrical assembly includes at least one capacitor device configured to supply energy to the computing unit for a period of time.

5 90. The assembly of claim 89 wherein the computing unit includes a real time clock/calendar and the at least one capacitor has a sufficiently large capacitance to supply, when fully charged, power requirements of the real time clock/calendar for a duration of at least about 30 minutes.

6 91. The assembly of claim 89 wherein at least one of: the at least one capacitor device and the computing unit, are located on the main circuit board.

7 92. The assembly of claim 86 wherein the elongated housing fits inside a circle having a diameter of no larger than about 1.0 inch.

8 93. The assembly of claim 86 wherein the elongated housing has a substantially tubular shape.

9 94. The assembly of claim 86 wherein the electrical assembly is further configurable to be connectable to a remote power source.

10 95. The assembly of claim 86 wherein the computing unit and the sensor operate on less than 4 volts.

11 96. The assembly of claims 86 wherein the one or more energy storage units comprises at least two AA cells in series.

12 97. The assembly of claim 86 wherein the electrical circuit comprises a flex circuit which is configured to run from the second end of elongated housing to the monitoring assembly in the first end of the housing.

13 98. The assembly of claim 86 wherein the computing unit is capable of directing the obtainment of sensor readings according to at least two different sampling schedules.

14  
99. The assembly of claim 87 wherein the cable is further connectable to an electrical connector on an end of the cable opposite the cable component, the connector configured for interconnecting the cable with one or more electronic devices.

15  
100. The assembly of claim 99 wherein the one or more electronic devices comprise at least one of: personal computer, a palm top computer, a protocol converter, and a communications device for communicating over a network.

16  
101. The assembly of claim 99 further including vent cap attachable to the connector.

17  
102. The assembly of claim 99 wherein the connector provides for communication signals employing RS-485 protocol.

18  
103. The assembly of claim 86 wherein the elongated housing is further configured to include a sensor component which is engageable and disengageable with the first end, the sensor component configured to include the at least one sensor positionable therein.

19  
104. The assembly of claim 103 wherein the sensor component and the first end are further configured such that the connection between the at least one sensor and the computing is established upon engagement of the sensor component with the first end.

20  
105. A tool assembly adapted for insertion into a well or other hole to direct monitoring of at least one condition existing in the well or other hole, the tool comprising:  
an elongated housing including a first end which comprises a removable sensor component configured to engage and disengage with the first end, the sensor component further including at least one sensor positionable therein, where the at least one sensor is configured to provide a sensor reading of at least one monitored condition, the sensor reading comprising a sensor output signal including sensor reading data corresponding to the at least one monitored condition;

said elongated housing further including a second end, where said second end includes an opening sized to receive and provide access to one or more energy storage units insertable therein;

a computing unit positioned within the elongated housing and connectable to the at least one sensor, the computing unit being configured to receive and process the sensor output signal;

a main circuit board positioned within the elongated housing, the main circuit board including at least one electrical contact positioned to contact one or more electrodes of the one or more energy storage units components upon insertion through the opening of the second end; and

an electrical assembly including the at least one electrical contact and an electrical circuit configured to conduct electrical signals between the second end of the elongated housing and the computing unit.

20  
21 106. The assembly of claim 105 wherein the sensor component and the first end are further configured such that the connection between the at least one sensor and the computing is established upon engagement of the sensor component with the first end.

20  
22 107. The assembly of claim 105 wherein the sensor component is rotatably engageable and disengageable with the first end of the elongated housing.

20  
23 108. The assembly of claim 105 further including a cable component configured for engaging and disengaging the second end of the elongated housing, where engagement of the cable component with second end establishes a connection with terminal end of a cable, the cable configured to include at least one of:

a plurality of communication lines which are operably connected through the electrical assembly with the computing unit so that the computing unit is capable of directing at least one communication function selected from (i) transmission of a communication signal via the

AI Cont  
communication lines and (ii) receiving a communication signal via the communication lines,  
a plurality of power lines which are operably connected to the computing and which  
conduct power from a remote power source; and

a first fluid conductive path extending along the length of the cable, such that when the  
elongated housing and cable component are assembled and the at least one sensor is a pressure  
sensor, the pressure sensor is capable of taking pressure readings adjusted for atmospheric  
pressure.

25/ 109. The assembly of claim 105 wherein the at least one electrical contact comprises a  
spring loaded contact extending from the main circuit board towards the second end of the  
elongated housing and positioned to contact one or more of the electrodes of the one or more  
energy storage units components upon insertion through the opening of the second end.

25/ 110. The assembly of claim 105 wherein the elongated housing fits inside a circle  
having a diameter of no larger than about 1.0 inch.

25/ 111. The assembly of claim 105 wherein the elongated housing has a substantially  
tubular shape.

21/ 112. The assembly of claim 105 wherein the electrical assembly includes at least one  
capacitor device configured to supply energy to the computing unit for a period of time.

26/ 113. The assembly of claim 112 wherein the computing unit includes a real time  
clock/calendar and the at least one capacitor has a sufficiently large capacitance to supply, when  
fully charged, power requirements of the real time clock/calendar for a duration of at least about  
30 minutes.

21/ 114. The assembly of claim 112 wherein at least one of: the at least one capacitor  
device and the computing unit, are located on the main circuit board.

30/ 115. The assembly of claim 105 wherein the electrical assembly is further configurable  
to be connectable to a remote power source.

31/ 116. The assembly of claim 105 wherein the computing unit and the sensor operate on  
less than 4 volts.

32/ 117. The assembly of claim 105 wherein the one or more energy storage units  
comprises at least two AA cells in series.

33/ 118. The assembly of claim 105 wherein the electrical circuit comprises a flex circuit  
which is configured to run from the second end of elongated housing, between the one or more

energy storage unit when inserted in the elongated housing and an interior surface of the elongated housing, to the monitoring assembly in the first end of the housing.

31 119. The assembly of claim 105 wherein the computing unit is capable of directing the obtainment of sensor readings according to at least two different sampling schedules.

35 120. The assembly of claim 108 wherein the cable is further connectable to an electrical connector on an end of the cable opposite the cable component, the connector configured for interconnecting the cable with one or more electronic devices.

35 121. The assembly of claim 120 wherein the one or more electronic devices comprise at least one of: personal computer, a palm top computer, a protocol converter, and a communications device for communicating over a network.

31 122. The assembly of claim 120 further including vent cap attachable to the connector.

35 123. The assembly of claim 120 wherein the connector provides for communication signals employing RS-485 protocol.

39 124. A tool assembly adapted for insertion into a well or other hole to direct monitoring of at least one condition existing in the well or other hole, the tool comprising:

an elongated housing with first and second ends, where the second end includes an opening sized to receive and provide access to one or more energy storage units insertable therein;

a computing unit positioned within the elongated housing and connectable to at least one sensor which is configured to provide a sensor reading of at least one monitored condition, the sensor reading comprising a sensor output signal including sensor reading data corresponding to the at least one monitored condition, the computing unit being configured to receive and process the sensor output signal;

a main circuit board positioned within the elongated housing, the main circuit board including at least one electrical contact positioned to contact one or more electrodes of the one or more energy storage units components upon insertion through the opening of the second end;

an electrical assembly including the at least one electrical contact and an electrical circuit configured to conduct electrical signals between the second end of the elongated housing and the computing unit; and

a removable cable assembly which is connectable to the second end so as to enclose the elongated housing and further configured to electrically interconnect with said electrical assembly, the removable cable assembly including a cable component with a housing portion for engaging and disengaging the second end of the elongated housing and a cable which terminates in the cable component and includes at least one: a first plurality of electrical conductors for carrying data signals, a second plurality of electrical conductors for carrying power signals.

40 125. The assembly of claim 124 wherein the cable component is a vented cable, having a first fluid conductive path extending along the length of the cable such that when the elongated housing and cable assembly are connected and the at least one sensor is a pressure sensor, the pressure sensor is capable of taking pressure readings adjusted for atmospheric pressure.

41 126. The assembly of claim 124 wherein the housing portion is configured to be rotatably engageable with the second end of the elongated housing.

42 127. The assembly of claim 124 further configured such that the engagement of the removable cable assembly with the second end of the elongated housing exerts sufficient compressive force between the at least one electrical contact and the one or more electrodes of

the one or more energy storage units so as to establish an electrical connection.

43 128. The assembly of claim 124 wherein the at least one electrical contact comprises a spring loaded contact extending from the main circuit board towards the second end of the elongated housing and positioned to contact one or more of the electrodes of the one or more energy storage units components upon insertion through the opening of the second end.

44 129. The assembly of claim 124 further wherein the electrical assembly includes at least one capacitor device configured to supply energy to the computing unit for a period of time.

45 130. The assembly of claim 129 wherein the computing unit includes a real time clock/calendar and the at least one capacitor has a sufficiently large capacitance to supply, when fully charged, power requirements of the real time clock/calendar for a duration of at least about 30 minutes.

46 131. The assembly of claim 129 wherein at least one of: the at least one capacitor device and the computing unit, are located on the main circuit board.

47 132. The assembly of claim 124 wherein the elongated housing fits inside a circle having a diameter of no larger than about 1.0 inch.

48 133. The assembly of claim 124 wherein the elongated housing has a substantially tubular shape.

49 134. The assembly of claim 124 wherein the electrical assembly is further configurable to be connectable to a remote power source.

50 135. The assembly of claim 124 wherein the computing unit and the sensor operate on less than 4 volts.

51 136. The assembly of claims 124 wherein the one or more energy storage units comprises at least two AA cells in series.

52 137. The assembly of claim 124 wherein the electrical circuit comprises a flex circuit which is configured to run from the second end of elongated housing to the monitoring assembly in the first end of the housing.

53 138. The assembly of claim 124 wherein the computing unit is capable of directing the obtainment of sensor readings according to at least two different sampling schedules.

54 139. The assembly of claim 124 wherein the cable is further connectable to an electrical connector on an end of the cable opposite the cable component, the connector configured for interconnecting the cable with one or more electronic devices.



35  
140. The assembly of claim 139 wherein the one or more electronic devices comprise at least one of: personal computer, a palm top computer, a protocol converter, and a communications device for communicating over a network.

36  
141. The assembly of claim 139 further including vent cap attachable to the connector.

37  
142. The assembly of claim 139 wherein the connector provides for communication signals employing RS-485 protocol.

38  
143. The assembly of claim 124 wherein the elongated housing is further configured to include a sensor component which is engageable and disengageable with the first end, the sensor component configured to include the at least one sensor positionable therein.

39  
144. The assembly of claim 143 wherein the sensor component and the first end are further configured such that the connection between the at least one sensor and the computing is established upon engagement of the sensor component with the first end.

60 145. A tool assembly adapted for insertion into a well or other hole to direct monitoring of at least one condition existing in the well or other hole, the tool comprising:

an elongated housing with first and second ends, where the second end includes an opening sized to receive and provide access to one or more energy storage units insertable therein;

at least one sensor positioned within the first end which is configured to provide a sensor reading of at least one monitored condition, the sensor reading comprising a sensor output signal including sensor reading data corresponding to the at least one monitored condition;

a computing unit positioned within the elongated housing and in electrical connection with the at least one sensor, the computing unit being configured to receive and process the sensor output signal;

a main circuit board positioned within the elongated housing, the main circuit board including at least one electrical contact positioned to contact one or more electrodes of the one or more energy storage units components upon insertion through the opening of the second end;

an electrical assembly including the at least one electrical contact and an electrical circuit configured to conduct electrical signals between the second end of the elongated housing and the computing unit; and

a removable cable assembly which is connectable to the second end so as to enclose the elongated housing and further configured to electrically interconnect with said electrical assembly, the removable cable assembly including a cable component with a housing portion for engaging and disengaging the second end of the elongated housing and a cable which terminates in the cable component and includes at least one: a first plurality of electrical conductors for carrying data signals, a second plurality of electrical conductors for carrying power signals.

61 146. The assembly of claim 145 wherein the first end is further configured to include a removable sensor component, wherein the at least one sensor is positionable within the sensor and the sensor component is configured to engage and disengage with the first end of the elongate housing.

62 147. The assembly of claim 145 wherein the sensor component is configured to provide for the electrical connection between the at least one sensor and the computing unit upon engagement of the sensor component with the first end of the elongate housing.

63 148. The assembly of claim 145 wherein the cable component is a vented cable, having

67  
60  
a first fluid conductive path extending along the length of the cable such that when the elongated housing and cable assembly are connected and the at least one sensor is a pressure sensor, the pressure sensor is capable of taking pressure readings adjusted for atmospheric pressure.

64 149. The assembly of claim 145 wherein the housing portion is configured to be rotatably engageable with the second end of the elongated housing.

65 150. The assembly of claim 145 further configured such that the engagement of the removable cable assembly with the second end of the elongated housing exerts sufficient compressive force between the electrical contacts and the electrodes of the one or more energy storage units so as to establish an electrical connection.

66 151. The assembly of claim 145 wherein the at least one electrical contact comprises a spring loaded contact extending from the main circuit board towards the second end of the elongated housing and positioned to contact one or more of the electrodes of the one or more energy storage units components upon insertion through the opening of the second end.

67 152. The assembly of claim 145 further wherein the electrical assembly includes at least one capacitor device configured to supply energy to the computing unit for a period of time.

68 153. The assembly of claim 152 wherein the computing unit includes a real time clock/calendar and the at least one capacitor has a sufficiently large capacitance to supply, when fully charged, power requirements of the real time clock/calendar for a duration of at least about 30 minutes.

69 154. The assembly of claim 152 wherein at least one of: the at least one capacitor device and the computing unit, are located on the main circuit board.

70 155. The assembly of claim 145 wherein the elongated housing fits inside a circle having a diameter of no larger than about 1.0 inch.

71 156. The assembly of claim 145 wherein the elongated housing has a substantially tubular shape.

72 157. The assembly of claim 145 wherein the electrical assembly is further configurable to be connectable to a remote power source.

73 158. The assembly of claim 145 wherein the computing unit and the sensor operate on less than 4 volts.

74 159. The assembly of claims 145 wherein the one or more energy storage units comprises at least two AA cells in series.

75 160. The assembly of claim 145 wherein the electrical circuit comprises a flex circuit which is configured to run from the second end of elongated housing to the monitoring assembly in the first end of the housing.

76 161. The assembly of claim 145 wherein the computing unit is capable of directing the obtainment of sensor readings according to at least two different sampling schedules.

77 162. The assembly of claim 145 wherein the cable is further connectable to an electrical connector on an end of the cable opposite the cable component, the connector configured for interconnecting the cable with one or more electronic devices.

78 163. The assembly of claim 162 wherein the one or more electronic devices comprise at least one of: personal computer, a palm top computer, a protocol converter, and a communications device for communicating over a network.

79 164. The assembly of claim 162 further including vent cap attachable to the connector.

80 165. The assembly of claim 162 wherein the connector provides for communication signals employing RS-485 protocol.

81  
166. A tool assembly adapted for insertion into a well or other hole to direct monitoring of at least one condition existing in the well or other hole, the tool comprising:  
an elongated housing with first and second ends, where the second end includes an opening;

a computing unit positioned within the elongated housing and connectable to at least one sensor which is configured to provide a sensor reading of at least one monitored condition, the sensor reading comprising a sensor output signal including sensor reading data corresponding to the at least one monitored condition, the computing unit being configured to receive and process the sensor output signal;

a main circuit board positioned within the elongated housing, the main circuit board including at least one electrical contact positioned to contact one or more components positionable within the second end of the elongated housing; and

an electrical assembly including an electrical circuit configured to conduct electrical signals between the second end of the elongated housing and the computing unit.

82 167. The assembly of claim 166 wherein the one or more components comprise at least one of: the electrical assembly and one or more energy storage units.

83 168. The assembly of claim 167 wherein the electrical assembly is further configurable to be connectable to a remote power source.

84 169. The assembly of claim 166 further including a cable component configured for engaging and disengaging the second end of the elongated housing, where engagement of the cable component with second end establishes a connection with terminal end of a cable, the cable configured to include at least one of:

a plurality of communication lines which are operably connected through the electrical assembly with the computing unit so that the computing unit is capable of directing at least one communication function selected from (i) transmission of a communication signal via the communication lines and (ii) receiving a communication signal via the communication lines,

a plurality of power lines which are operably connected to the computing and which conduct power from the remote power source; and

a first fluid conductive path extending along the length of the cable, such that when the elongated housing and cable component are assembled and the at least one sensor is a pressure sensor, the pressure sensor is capable of taking pressure readings adjusted for atmospheric

pressure.

85  
170. The assembly of claim 166 further configured such that the engagement of the cable component with the elongated housing exerts sufficient compressive force between the at least one electrical contact and the one or more components so as to establish an electrical connection.

86  
171. The assembly of claim 166 wherein the at least one electrical contact comprises a spring loaded contact extending from the main circuit board towards the second end of the elongated housing and positioned to contact the one or more components positionable in the second end.

81  
172. The assembly of claim 166 further wherein the electrical assembly includes at least one capacitor device configured to supply energy to the computing unit for a period of time.

88  
173. The assembly of claim 172 wherein the computing unit includes a real time clock/calendar and the at least one capacitor has a sufficiently large capacitance to supply, when fully charged, power requirements of the real time clock/calendar for a duration of at least about 30 minutes.

81  
174. The assembly of claim 172 wherein at least one of: the at least one capacitor device and the computing unit, are located on the main circuit board.

90  
175. The assembly of claim 166 wherein the elongated housing fits inside a circle having a diameter of no larger than about 1.0 inch.

91  
176. The assembly of claim 166 wherein the elongated housing has a substantially tubular shape.

92  
177. The assembly of claim 166 wherein the computing unit and the sensor operate on less than 4 volts.

93  
178. The assembly of claims 167 wherein the one or more energy storage units comprises at least two AA cells in series.

94  
179. The assembly of claim 166 wherein the electrical circuit comprises a flex circuit which is configured to run from the second end of elongated housing to the monitoring assembly in the first end of the housing.

95  
180. The assembly of claim 166 wherein the computing unit is capable of directing the obtainment of sensor readings according to at least two different sampling schedules.

96  
181. The assembly of claim 169 wherein the cable is further connectable to an

electrical connector on an end of the cable opposite the cable component, the connector configured for interconnecting the cable with one or more electronic devices.

182. The assembly of claim 181 wherein the one or more electronic devices comprise at least one of: personal computer, a palm top computer, a protocol converter, and a communications device for communicating over a network.

183. The assembly of claim 181 further including vent cap attachable to the connector.

184. The assembly of claim 181 wherein the connector provides for communication signals employing RS-485 protocol.

185. The assembly of claim 186 wherein the elongated housing is further configured to include a sensor component which is engageable and disengageable with the first end, the sensor component configured to include the at least one sensor positionable therein.

186. The assembly of claim 185 wherein the sensor component and the first end are further configured such that the connection between the at least one sensor and the computing is established upon engagement of the sensor component with the first end.